

This drawing, specifications, and concepts contained herein are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

	REVISIONS									
REV	DESCRIPTION	DATE	INITIAL	APPROVED						
Α	CH'D TITLEBLOCK & REVISION BLOCK, ADDED ENGRAVE NOTE, ADDED .030 x 45' CHAMFER P/N $-1$ PER D.W.	11/20/09	RJC	RW						
В	CH'D -1 MATERIAL FROM CR 4140 PER D.W, CORRECTED MINOR DIAMETER TO MAJOR DIAMETER IN THE SPLINE DATA TABLE.	9/20/12	RJC	GE						

SOCKET



SPLINE	DATA		
TYPE	EXTERNAL		
NO OF TEETH	36		
DAMETRAL PITCH	20		
PRESSURE ANGLE	20°		
MAJOR DIAMETER	1,890±,002		
DIAMETER OVER			
.086 PINS (4)	1.904-1.909		



## WELDMENT RED BARN MACHINE **ENGINE** TURNING DWG NO. 269T1005 В UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES DECIMALS .XXX ± .005 .XXX ± .01 X ± .01 ANGLES ± .5\* DRAWN BY COLE APPROVED D Weil

10-26-01

BLACK DXIDE USED ON MODEL

1 of

HUGHES 269 SCHWEIZER 300

SHEET

FRACTIONS ± 1/32

DATE

UNLESS DTHERWISE SPECIFIED

1. BREAK ALL SHARP EDGES

015 × 45° PR 015 R

2. DIMENSIONAL LIMITS APPLY AFTER PLATING

SCALE

 $\omega$ 16

## NOTE:

- 1. IF AVAILBLE USE SCRAP 269A5559 BELT DRIVE. ANNEAL BEFORE MACHINING. TURN STUB OFF Ø13/16 x 3/8-5/8 LONG.
- 2. IF UNAVAILABLE TURN OD TO SIZE, SEND OUT FOR SPLINNING, CUT TO LENGTH & FACE. ASSEMBLE WITH SOCKET AND WELD.

ASS' QT'	YASSY 'QTY	B/0	PART 1	# QTY	DESCRIPTION	MATERIAL	B/O INFORMATION OR SPECIFICATIONS
	1		-1		GEAR	4140	Ø2 x 7/8
	1	B/0	-3		SOCKET		1/2 DR. 13/16 UNCOATED OR BLACK - PROTO #7426H
	$\times$		-5	1	WELDMENT		
	ASSY -5						

